

Multi Gas Clip Infrared

The first portable multi gas detector
with a battery life of months instead of hours



- Operates for 2 months continuously on a single charge
- Detects combustible gases (LEL), hydrogen sulfide (H₂S), carbon monoxide (CO) & oxygen (O₂)
- 1-year calibration cycle saves test gas & valuable time
- Infrared LEL sensor does not require oxygen to detect gas
- Low maintenance cost - infrared LEL sensor is immune to poisons
- Simple-to-use one-button operation - large, easy-to-read screen
- Lightweight & durable - alligator clip clamps on tight

Bump testing before each day's use is advised.

*All detectors are charged and calibrated during manufacturing.

gasclip
technologies

Portable Gas Detectors You Can Count On

gascliptech.com • +1.972.775.7577 • Toll-free: 1.877.525.0808
email: info@gascliptech.com

Multi Gas Clip Versions

Multi Gas Clip Infrared Part# MGC	Infrared four gas detector H ₂ S, CO, O ₂ & LEL
Multi Gas Clip Pellistor Part# MGC-P	Pellistor four gas detector H ₂ S, CO, O ₂ & LEL

Included with all detectors: charger, calibration cap, calibration certification & Quick Start Guide

Multi Gas Clip Accessories



Multi Gas Clip Dock

Part# MGC-DOCK*

High Pressure Part# MGC-DOCK-HP



Multi Gas Clip Wall Mount Dock

Part# MGC-WMDOCK*

High Pressure Part# MGC-WMDOCK-HP



MGC Confined Space Kit w/Gas

Part# MGC-CSK-GAS*

Kit Without Gas Part# MGC-CSK



Quad Gas Cylinders

25ppm H₂S, 100ppm CO, 18% O₂ & 50% LEL

58L Part# MGC-Q-58 or 116L Part# MGC-Q-116



GCT IR Link

Part# GCT-IR-LINK



MGC Vehicle Charger

Part# MGC-V-CHARGER1



MGC Multi Charger

Part# MGC-CHRG-MULTI



MGC Hand Aspirator Kit

Part# MGC-HAK

*Detector(s) not included

Please contact Gas Clip Technologies for additional spares, accessories and gas.

Distributed by:

EndoMatrix (M) Sdn Bhd
No. 51-5, Block G, Dataran Prima, Jalan PJU 1/37,
47301 Petaling Jaya, Selangor Darul Ehsan, Malaysia.
Phone: 03-7803 1145 I Fax: 03-9101 4814
sales@endomatrix.com.my I www.endomatrix.com.my

SPECIFICATIONS

Size • Weight	4.7" H x 2.4" W x 1.2" D (118.6 x 61.6 x 31.7 mm) • 7.7 oz. (240 g)
Temperature	-4° to +122°F (-20° to +50°C)
Humidity	5% to 95% RH (non-condensing)
Battery Life	Infrared versions.....60 days (continuous) Pellistor versions.....25 hours (typically)
Charge Time	4 - 6 hours
Alarms	Visual, vibrating & audible (minimum 95 dB) Low, High, STEL, TWA & OL (Over Limit)
LEDs	4 Red alarm bar LEDs Yellow back-light (activated on button press) Red back-light (activated on alarm condition) Yellow maintenance notification LED
Display	High viewing angle alphanumeric Liquid Crystal Display (LCD)
Logs	25 Bump tests 25 Events 25 Calibrations Continuous 1-second data logging (typical capacity > 2 months)
Tests	Full-function self-test upon activation Sensors, battery and circuitry tests run continuously
Ratings	EMC Directive 2004/108/EC IP 67

Certifications and Approvals



CSA: CSA13CA0014

Intrinsically Safe/Sécurité Intrinsèque
Class I, Division 1, Group A, B, C and D

• **MGC (IR), MGC-2 (discontinued):** Ex ia IIC T4 Ga

Class I, Zone 0, AEx ia IIC T4 Ga

• **MGC-P (MEMS):** Ex da ia IIC T4 Ga

Class I, Zone 0, AEx da ia IIC T4 Ga

• **MGC-P (KNC), MGC-2-P (discontinued):** Ex db ia IIC T4 Gb

Class I, Zone 1, AEx db ia IIC T4 Gb

-20°C ≤ Ta ≤ 50°C; 4.2 Vdc

ANSI/ISA 12.13.01-2000

C22.2 No 152 - M1984

C22.2 No 60079-0:11

C22.2 No 60079-11:11

IECEX: IECEX CSA 13.0014

• **MGC (IR), MGC-2 (discontinued):** Ex ia IIC Ga

• **MGC-P (MEMS):** Ex da ia IIC T4 Ga

IEC 60079-1:2014-06 Edition: 7.0

• **MGC-P (KNC), MGC-2-P (discontinued):** Ex db ia IIC T4 Gb

IEC 60079-1:2014-06 Edition: 7.0

-20°C ≤ Ta ≤ 50°C

IEC 60079-0:2011 Edition: 6.0

IEC 60079-11:2011 Edition: 6.0

• **ATEX:** SIRA 14ATEX2013

• **MGC (IR), MGC-2 (discontinued):** Ex ia IIC T4 Ga

• **MGC-P (MEMS):** Ex da ia IIC T4 Ga

• **MGC-P (KNC), MGC-2-P (discontinued):** Ex db ia IIC T4 Gb

-20°C ≤ Ta ≤ 50°C

EN 60079-0:2012/A11

EN 60079-11:2012

EN 60079-26:2007

EN 60079-1:2014



Warranty

Full 2 years

Gases

H₂S.....0 - 100 ppm (0.1 ppm increments)

CO.....0 - 500 ppm (1 ppm increments)

Combustible (LEL)...0 - 100% LEL (0.1% increments)

O₂.....0 - 30% vol. (0.1% increments)

Sensor Type

H₂S, CO & O₂.....Plug-in electrochemical cell

Combustible (LEL)...Plug-in infrared or pellistor

Recommended

Calibration Frequency

Infrared versions.....1 year

Pellistor versions.....6 months



USER OPTIONS

Custom user message	Maintenance notification
TWA/STEL intervals	TWA method
Languages (6)	Sensor enable/disable
Latching alarms	SAFE display
Self-test lock	Dock lock
Auto-zero on start up	Calibration gas percentage
Bump test interval	Calibration interval
Low/High alarm	TWA/STEL alarm
Off-Lock	% LEL or % CH4 by-vol

Specifications are subject to change without notice due to ongoing product development.

Copyright © 2022 Gas Clip Technologies, Inc. All Rights Reserved

MGC v3.12