

mc50 duoSet

for pipes from 50 to 400 mm

**different camera heads
for your selection**



for pipes from 50 to 400 mm


mc50duoSet

for pipes from 50 to 400 mm

2-in-1 dual-reel sewer, water & drain video pipe inspection system, with outer & inner cable reel, and sunlight-readable monitor.
The mc50 Duo dual-reel system comes with two cameras attached to two separate cable reels built into one complete maintenance free CCTV push system.
Application range is 50 to 400 mm (with all optional accessories). 512 Hz sonde or 33 kHz available for special order.

kk29sl camera head		kk55sl camera head	
	<ul style="list-style-type: none"> • Self leveling camera head • high res color camera module • 480 TV-lines; 0.02 lux • 3 mm Sapphire protected lens • 10 bar water protected • view angle diagonal: 140° • Outer diameter: 29 mm • cylindrical length: 16 mm 		<ul style="list-style-type: none"> • Self leveling camera head • high res color camera module • 480TV-lines; 0.05 lux • 4 mm Sapphire protected lens • 10 bar water protected • view angle diagonal: 120° • Outer diameter: 55 mm • cylindrical length: 36 mm

mc50 monitor		mc50 Set	
	<ul style="list-style-type: none"> • 8.4" sunlight readable TFT-LCD monitor in a robust Peli Stormcase • ergonomically mounted on the reel • storage of videos, pictures and audio on SD-card – max. 32 GB • MPEG-4 video (*.avi; 800 x 600 pixel) • Pictures (*.bmp; 640 x 480 pixel) • electronic insert on meter value, date (text generator optional) 		<ul style="list-style-type: none"> • cable reel out of stainless steel and carbon • 20 m / 6.7 mm push rod changeable due to a special connector • 60 m / 9.2 mm push rod changeable due to a special connector • control unit with function keys for meter counter (sonde optional) • continuous light regulation, battery status • BNC video out • internal power supply 100 – 240 V 12 V car charger; battery > 2 h

mc50Set the small brother for pipes from 70 to 400 mm	
	<ul style="list-style-type: none"> • Only outer reel rim with KK55SL • dimension: 645 x 300 x 665 mm (L x w x h) • weight of mc50Set: about 16 kg



minCam GmbH
Gruben 1 • 87561 Oberstdorf, Germany
Telefon +49 (0)8326 384122
info@minCam.de • www.minCam.de

EndoMatrix (M) Sdn Bhd
No. 51-5, Block G, Dataran Prima, Jalan PJU 1/37,
47301 Petaling Jaya, Selangor Darul Ehsan, Malaysia.
Phone: 03-7803 1145 | Fax: 03-9101 4814
sales@endomatrix.com.my | www.endomatrix.com.my