

mc80SET

for pipes from 100 to 400 mm

**different camera heads
for your selection**





for pipes from 100 to 400 mm

mc80_{SET}

for pipes from 100 to 400 mm

This optical inspection system is the biggest from the mc-family. The mainline-manhole to manhole camera with a rod length of 130 m standard is built for mainline push camera inspection. Constructed with wheels it is easy to handle and absolutely robust for this application.

kk55sl camera head	mc80 monitor
 <ul style="list-style-type: none"> • Self leveling camera head • high res color camera module • 480 TV-lines; 0.05 lux • 4 mm Sapphire protected lens • 10 bar water protected • view angle diagonal: 120° • Outer diameter: 55 mm • cylindrical length: 36 mm 	 <ul style="list-style-type: none"> • 8.4" sunlight readable TFT-LCD monitor in a robust Peli Stormcase • ergonomically mounted on the reel • storage of videos, pictures and audio on SD-card – max. 32 GB • MPEG-4 video (*.avi; 800 x 600 pixel) • Pictures (*.bmp; 640 x 480 pixel) • electronic insert on meter value, date (text generator optional)

mc80 Set	mc80 spacers
 <ul style="list-style-type: none"> • cable reel out of stainless steel and carbon • 130 m / 11.2 mm push rod changeable due to a special connector • Control unit with meter counter function keys • sonde for 512 Hz or 33 kHz • continuous light regulation, battery status • BNC video out • internal power supply 100 – 240 V; 12 V car charger adapter, battery > 3 h 	<ul style="list-style-type: none"> • spacer 75 mm • roller skid >130 mm with exchange rolls for more than 200 mm • roller skid > 250 mm • dimension with wheels: 730 x 375 x 780 mm (l x w x h) • weight: about 29 kg 



minCam GmbH
Gruben 1 · 87561 Oberstdorf, Germany
Telefon +49 (0)8326 384122
info@minCam.de · www.minCam.de

EndoMatrix (M) Sdn Bhd
No. 51-5, Block G, Dataran Prima, Jalan PJU 1/37,
47301 Petaling Jaya, Selangor Darul Ehsan, Malaysia.
Phone: 03-7803 1145 | Fax: 03-9101 4814
sales@endomatrix.com.my | www.endomatrix.com.my